



NO HAZMAT FUEL & SERVICE TRAILERS

460 | 690 | 920 GALLONS



NO CDL. NO HAZMAT. NO PROBLEM.

The Multi-Tank Trailer from Thunder Creek is the first fuel and service trailer to legally mitigate the need for the driver to have a HAZMAT endorsement.* In many cases, a CDL is also not required.

The trailers can be configured with our patented four, six or eight non-spec, 115 gallon fuel tanks. Each tank stands alone as a DOT compliant, non-bulk, diesel fuel tank capable of being transported without a HAZMAT. Tanks are joined via a manifold to a common pump allowing for complete isolation during transport as well as controlled dispensing of fuel at the job site. An electric valve manifold option automatically closes the manifold to ensure DOT Compliance without operator intervention.

The MTT Signature Package features our most popular options and features a NEW stationary side step for easier access to tank fill ports**. This package also includes a gas-powered pump upgrade, rear utility box, and our patented, 2-way, closed, ISO compliant, 100 gallon DEF system.

*Per the Code of Federal Regulations, Title 49 (CFR49). The Multi-Tank Trailer specifically uses independent non-bulk packaging for the transportation of combustible liquids in the U.S. Contact us for details about state regulations.

**The stationary side step can be added to all MTT models except the MTT460.

**LEGALLY
TRANSPORT
BULK DIESEL
WITHOUT A
HAZMAT**



FUEL | DEF | SERVICE | LUBE



NO HAZMAT FUEL & SERVICE TRAILERS

LEGALLY TRANSPORT DIESEL FUEL WITHOUT A HAZMAT*

**INDUSTRY LEADING
3 YEAR TANK
WARRANTY**

FEATURED MODEL: MTT920



STANDARD FEATURES

TRAILER FEATURES

- Dual Coat Grey Polyurethane Paint
- Diamond Plate Rock Guard on Fenders & Frame
- Replaceable Bolt-on Fenders
- Lockable Hatch-Style, Weather-Sealed Doors
- Dexter® Torsion Axles and EZ Lube Hubs
- Self Adjusting Electric Brakes
- Breakaway Safety System
- 10-Ply Tires, ST235/80R16, Load Range E with Steel Wheels
- 7,000 lb. Enclosed Jack
- Safety Tow Chains
- Adjustable Height 2 5/16" Ball Hitch
- 7.5" x 1/4" Formed Frame
- Reflective Tape
- Automatic Interior LED Lighting
- Wiring Wrapped in Protective Braid
- Fire Extinguisher

TANKS AND PUMPING SYSTEM

- 115 Gallons per Tank, up to 8 Tanks
- 7 Gauge, Sloped Floor Steel Tanks
- Tank Vents
- Spinsecure™ Locking Fuel Caps
- 12V Deep Cycle Marine Battery
- 12' Power Cables
- 35' x 1" Retracting Hose Reel
- Auto-Trip Nozzle
- Extruded Aluminum Pump Manifold
- 25 GPM Industrial Grade 12V Pump
- Sight Fuel Level Gauges
- 10 Micron Fuel Filter

OPTIONS

Items with + can be added any time to expand the functionality of the trailer as your operation grows.

SIGNATURE PACKAGE

- Gas Powered Pump Upgrade
- 100 Gallon DEF Tank, Pump and 35' Reel +
- Aluminum Wheels
- 14-Ply Tires, ST235/85R16, Load Range G
- Electric/Hydraulic Jack +
- Solar Battery Maintainer +
- Electric Valve Manifold for Automatic Shut-Off
- Stationary Side Step +
- *Not available on MTT460

ADDITIONAL OPTIONS

- WorkSight Light Tower +
- Spare Tire Kit with 10 or 14-Ply Tires +
- Digital or Analog Fuel Meter +
- 50' Fuel Hose Reel Upgrade
- 50' Static Discharge Reel +
- Spill Containment Kit +
- Digital DEF Meter +
- 50' DEF Hose Reel Upgrade
- 120V DEF Tank Heater +
- 2 Stage Filter System (10+4 Micron) Upgrade
- Pintle Hitch +
- Compressed Air Connection at Hitch
- Custom Color

REAR UTILITY BOX OPTIONS

- Rear Utility Box (41.75"d x 58.75"w x 49.75"h) +
- Five Drawer Tool Chest for Utility Box +
- Two Drawer Low Boy Tool Chest +
- Can+Towel Holder +
- Work Bench with Vise +
- 35 lb. Pneumatic Grease Kit +
- Welder+Comp+Gen with 50' Air/Elec. Combo Reel +
- Comp+Gen with 50' Air/Elec. Combo Reel +
- Air Compressor with 50' Air Hose Reel +
- 20' Weld Cable Extension +
- 50' Weld Cable Extension +

SPECIFICATIONS

Shown with optional aluminum wheels

Model	MTT460	MTT690	MTT920
115 Gallon Tanks	4 tanks 460 gal. total 7 gauge	6 tanks 690 gal. total 7 gauge	8 tanks 920 gal. total 7 gauge
Torsion Axles Hubs	dual 5,000 lbs. axles 8 bolt hubs	dual 6,000 lbs. axles 8 bolt hubs	dual 7,000 lbs. axles 8 bolt hubs
L W H*	13' 7' 6'	16' 7' 6'	18' 7' 6'
Empty Weight* GVWR	3,650 lbs. 10,000 lbs.	4,500 lbs. 12,000 lbs.	5,300 lbs. 14,000 lbs.

*A rear utility box adds 3'4" to the length and 650 lbs. to the empty weight.